

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
24 February 2000 (24.02.2000)

PCT

(10) International Publication Number  
**WO 00/10348 A3**

(51) International Patent Classification<sup>7</sup>: **H04Q 7/22**

[FI/FI]; Nissnikuntie 7 B 5, FIN-02430 Masala (FI).  
**HOLMA, Harri** [FI/FI]; Itätuulenkuja 1 B 32, FIN-02100  
Espoo (FI).

(21) International Application Number: **PCT/FI99/00670**

(22) International Filing Date: 12 August 1999 (12.08.1999)

(74) Agent: **PATENTTITOIMISTO TEKNOPOLOIS KOL-  
STER OY**; C/O Kolster Oy AB, Iso Roobertinkatu 23, P.O.  
Box 148, FIN-00121 Helsinki (FI).

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:  
981757 14 August 1998 (14.08.1998) FI

(81) Designated States (*national*): AE, AL, AM, AT, AT (util-  
ity model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN,  
CR, CU, CZ, CZ (utility model), DE, DE (utility model),  
DK, DK (utility model), DM, EE, EE (utility model), ES,  
FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID,  
IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT,  
LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ,  
TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*): **NOKIA  
NETWORKS OY** [FI/FI]; Keilalahdentie 4, FIN-02150  
Espoo (FI).


(72) Inventors; and

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,

(75) Inventors/Applicants (*for US only*): **RAITOLA, Mika**

[Continued on next page]

(54) Title: **PACKET-SWITCHED DATA TRANSMISSION IN RADIO SYSTEM**



(57) Abstract: The invention relates to a method of transmitting packet-switched data and a radio system comprising a transmitter (112, 114) and a receiver (116) arranged to transmit packet-switched data, and in which the connection (122, 124) between the transmitter and the receiver comprises at least two logical channels, and in which the transmitter and the receiver are arranged to use one logical channel for transmitting delay-critical information, and that the transmitter and the receiver are arranged to transmit the information as located in given transmission units and to employ the method of error protection in the transmission of the transmission units. In the solution of the invention the transmitter (112, 114) and the receiver (116) are arranged to employ a different method of error protection when transmitting data an delay-critical information. By means of the invention, services requiring fast transmission of high quality, such as speech and packet data, can be transmitted simultaneously as multiplexed.

WO 00/10348 A3